

# B-PRIMIS ET-PRIME 15

## INFORMATION TECHNICAL DATA

B-Primis ET-Prime 15	Specification
Description	ET-Prime 15 S02
Order number	<b>S-01010203-0208</b>
Dimensions WxHxD [mm]	392 x 241 x 55
Display diagonals / Resolution	15,6" display / 1920 x 1080 (WXGA)
Touch type	Capacitive
Colours	TFT: 16,7 M (24 Bit/Pixels)
Weight	approx. 3 kg
Mounting	Removable securing clips
Certification	CE (EN 61131-2)
CPU	800 MHz ARM CPU mit Cortex™-A9 Single Core
RAM / Flash storage	512 MB RAM / 2GB Flash
Communication interfaces	1x Ethernet, 10/100 Base, RJ45
Visualization	Target Visu (VNC Client), Web Visu (Web Client, HTML5)
Additional features	1x Host USB 2.0 / USB plug type A
Supply voltage	+24 VDC (-15% / +20%) SELV max. AC voltage component 5% with reverse voltage protection
Current consumption	Max. 0.9 A at +24 VDC
Operating conditions Transport / Storage	Ambient temperature: operational: 0 °C to 55 °C / transport -20 °C to +70 °C Relative humidity: max. 85%, non-condensing
<b>EMC, protection type</b>	
Emitted Interface	EN 61000-6-4, industrial area
Immunity to interface	EN 61000-6-2, industrial area
Protection class	III
Insulation strength	EN 61131-2
Protection type	IP20, front IP55
Vibration	Sinusodial (EN 60068-2-6) test: Fc; 10 ... 150 Hz, 1 G (operation mode)
Schock resistance	15 G (approx. 150 m/s <sup>2</sup> ), 10 ms duration, half-sine (EN 60068-2-27) test: Ea

You can reach us at:

T: +49.7121.894-0 | E: [controls@berghof.com](mailto:controls@berghof.com)

Berghof Automation GmbH | Arbachtalstraße 26 | 72800 Eningen u.A.

[www.berghof-automation.com](http://www.berghof-automation.com) | Subject to changes and errors

