

B-PRIMIS DC-PRO 10

INFORMATION TECHNICAL DATA

B-Primis DC-Pro 10	Specification				
	DC-Pro 10 S01	DC-Pro 10 S02	DC-Pro 10 S03	DC-Pro 10 S04	DC-Pro 10 S05
Order number	S-01010103-0105	S-01010103-0205	S-01010103-0305	S-01010103-0405	S-01010103-0505
Order number Dualcore	-	-	-	S-01010103-2405	S-01010103-2505
Dimensions WxHxD [mm]	278,9 x 195,5 x 56				
Display diagonals/ resolution	10,1" Display / 1280 x 800 (WXGA)				
Touch operation	Resistive				
Colours	TFT: 16,7 M (24 Bit/Pixels)				
Weight	approx. 2,5 Kg				
Mounting	bolt mounting, additional option with securing clips for front IP65				
Certification	CE (EN 61131-2)				
CPU	800 MHz ARM® CPU with Cortex™-A9 Single Core / Dualcore: 800 MHz ARM® CPU mit Cortex™-A9				
RAM / Flash / Retain	512 MB RAM 512 MB Flash 100 kB Retain		512 MB RAM 1 GB Flash 100 kB Retain	512 MB RAM 2 GB Flash 100 kB Retain	
Dualcore	-	-	-	1 GB RAM 2 GB Flash 100 kb FRAM	1 GB RAM 2 GB Flash 100 kb FRAM
Communication interfaces	1x Ethernet, 10/100 Base, RJ45				
	1x EtherCAT, RJ45				
	-	-	1x CAN Bus, RJ45	2x CAN Bus, RJ45	
	-	-	-	1x RS232/485 combo	
Protocols	Standard: EtherCAT Master, CANOpen Master, NTP, FTP Optional: Modbus RTU/TCP, SNMP, OPCuA, J1939, Ethernet/IP, PROFINET, BACnet, KNX, IoT				
Visualization	Target Visu (Display), Optional: Web Visu (Web Server, HTML5)				
Additional features	2x Host USB 2.0 / USB plug type A				
	1x RTC, battery buffered				
	- - - 1x Micro SD-Card slot up to 32 GB				
Digital I/O´s	4x digital input, 4x digital output (0,5A)				
Analogue I/O´s	- 4x analog input (-10V..+10V, 2x PT100/PT1000) Resolution: 24 Bit				
Supply voltage	+24 VDC (-15% / +20%) SELV max. AC voltage component 5% with reverse voltage protection				
Current consumption device	Max. 0.8 A at +24 VDC				
Current consumption dig. outputs	depending on output load, continuous max. 2.7 A				
Operating conditions Transport / storage	Ambient temperature: operational: 0 °C to 55 °C / transport -20 °C to +70 °C Ambient temperature: operational Dualcore: 0 °C to 50 °C / transport -20 °C to +70 °C Relative humidity: max. 85%, non-condensing				

You can reach us at:
T: +49.7121.894-0 | E: controls@berghof.com
Berghof Automation GmbH | Arbachtalstraße 26 | 72800 Eningen u.A.
www.berghof-automation.com | Subject to changes and errors



B-PRIMIS DC-PRO 10

INFORMATION TECHNICAL DATA

B-Primis DC-Pro 10	Specification				
Description	DC-Pro 10 S01	DC-Pro 10 S02	DC-Pro 10 S03	DC-Pro 10 S04	DC-Pro 10 S05
EMC, Protection type					
Emitted interference	EN 61131-2; EN 61000-6-4, industrial area				
Immunity to interference	EN 61131-2; EN 61000-6-2, industrial area				
Protection class	III				
Insulation strength	EN 61131-2				
Protection type	IP20, front IP54 (IP65 only with all securing clips attached)				
Vibration	Sinusoidal (EN 60068-2-6) test: Fc; 10 ... 150 Hz, 1 G (operation mode)				
Schock resistance	15 G (ca. 150 m/s ²), 11 ms duration, half-sine (EN 60068-2-27) test: Ea				

You can reach us at:

T: +49.7121.894-0 | E: controls@berghof.com

Berghof Automation GmbH | Arbachtalstraße 26 | 72800 Eningen u.A.

www.berghof-automation.com | Subject to changes and errors

